

New Thermo Scientific RadEye G Ex radiation detector series, used by e.g. emergency services, fire fighters and hazmat teams for safe measurements in potentially explosive atmospheres.

Thermo Scientific RadEye G Ex series



Intrinsically Safe Personal Radiation Detectors



Key Features and Benefits

- Efficient and reliable dose and dose rate measurements
- Intrinsically safe according to ATEX standards
- Large, clear and backlit display for error free readings
- Rugged and reliable
- Light-weight, only 160 g (5.6 oz)
- Low power technology

Applications

- Emergency services
- Fire brigades
- Hazmat teams
- Locations with risk of explosion
- Refineries
- Oil platforms

In emergency response and in industry flammable and explosive materials like gases, dust and fibers can occur. In such potentially explosive atmospheres it is necessary to use ATEX certified devices for your measurements.

The Thermo Scientific RadEye G Ex radiation detector series comprises 4 versions of intrinsically safe handheld devices for gamma and dose rate measurements. They are designed according to the latest ATEX standards to meet the needs of their operator in and around hazardous areas.

The dose rate capabilities of the high range RadEye versions GF-Ex and GF-10-Ex radiation detectors are designed to exceed the higher set points required for "Emergency Response Life-Saving Turn Around" situations.

Devices certified as „intrinsically safe“ are designed to be unable to release sufficient electrical or thermal energy to cause ignition of flammable materials like gas, dust or particulates.

Beside the ATEX tags, the visual difference between the RadEye detector versions is noted by the orange color of the front panel of the intrinsically safe versions for increased visual impact in reduced visibility situations.

Inside, the RadEye G Ex detector devices have been re-engineered to reduce energy safety issues and avoiding the generation of heat and electrical sparks. They are premium products designed for ultimate safety and accurate dose rate measurements.

ATEX Certification RadEye G Ex Instruments



	ATEX examination mark. This sign is required on all devices used in European hazardous areas.
II 2G	Classification of zones. II = device is approved for all non-mining areas. 2 = category of the device, here it means that the device is rated for the second most hazardous areas. G = designates atmosphere, in this case gas, vapors and mist.
Ex	Explosion protection based on European Ex-regulations.
ia	Explosion protection type, „ia“ is the highest level of protection.
IIB	Gas group for average reactive gases (except hydrogen, acetylene or disulfide)
T4	Temperature class gives the user the maximum temperature of a surface that may be in contact to the Ex atmosphere under fault conditions. T4 is rated at 135°C.

Specifications

SI-units

USA

Measuring range	RadEye G-10-Ex: From 0.5 µSv/ to 100 mSv/h RadEye GF-10-Ex: From 5 µSv/h to 3 Sv/h	RadEye G-Ex: From 50 µR/h to 10 R/h RadEye GF-Ex: From 0.5 mR/h to 300 R/h
Sensitivity (Cs-137, 660 keV)	RadEye G-10-Ex: ~1.7 cps/µSv/h RadEye GF-10-Ex: ~0.13 cps/µSv/h	RadEye G-Ex: ~17 cps/mR/h RadEye GF-Ex: ~1.3 cps/mR/h
Dose	0.5 µSv to 10 Sv [50 µR to 1000 R]	
Linearity error	max. +/- 10 % in the measuring range	
Alarm thresholds	Two each thresholds for dose and dose rate	
Energy range	48 keV - 3 MeV according to IEC60846-1 and ANSI 42.17A accordingly	
Working temperature	-20°C ... + 50°C	
Relativ humidity	10 ... 90 % at 35°C	
Protection degree	IP 65 according to EN 60 529	
ATEX classification	II 2G Ex ia IIB T4 IBExU10ATEX1096	
Size	96 x 61 x 31 mm without rubber protector	
Weight	approx. 160 g, including 2 batteries	
Internal memory	The latest 1600 measured values are saved and can be read out via PC-program. Logbook with 250 entries for changes of configuration, occurring alarms and errors.	

Order numbers

RadEye G-10-Ex:	425067660	RadEye G-Ex:	425067460
RadEye GF-10-Ex:	425067670	RadEye GF-Ex:	425067470

© 2011 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Results may vary under different operating conditions. Thermo Fisher Scientific makes no warranties, expressed or implied, in this product summary. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representatives for details. LIT110615_DB_RadEyeG_Ex -e-V1.2

Europe, Africa, Middle East & Countries Not Listed

Frauenauracher Strasse 96 +49 (0) 9131 998-226
D 91056 Erlangen, Germany +49 (0) 9131 998-172 fax
customerservice.eid.erlangen@thermofisher.com

China

7th Floor, Tower West, Yonghe Plaza +86 10 8419 3588
No. 28 Andingem E. Street, Beijing, 100007 China +86 10 8419 3581 fax
info.eid.china@thermofisher.com

Singapore

11 Biopolis Way, Helios, Units #12-07/08 +65 6478 9728
Singapore 138667 +65 6478 9505 fax
info.eid.singapore@thermofisher.com

United Kingdom

Bath Road, Beenham, +44 (0) 118 971 5042
Reading RG7 5PR United Kingdom +44 (0) 118 971 2835 fax
customerservice.eid.beenham@thermofisher.com

USA, Canada, Mexico, Central & South America

27 Forge Parkway +1 (508) 553 1700
Franklin, MA 02038 USA +1 (800) 274 4212 US toll-free
info.eid@thermofisher.com +1 (508) 520 2815 fax

India

Plot No. C -327, T.T.C. Industrial Area, Pawne +91-22-41578800
Navi Mumbai 400 705, India +91-22-41578801 fax
info.eid.india@thermofisher.com

www.thermoscientific.com/rmp

