

New highly sensitive Thermo Scientific radiation detector system for fast discrimination between natural and artificial gamma radiation.

Thermo Scientific RadEye NBR

Portable high-sensitivity gamma radiation monitor



Operational areas

- First responders / Fire brigades
- Security professionals
- Environmental monitoring
- Remediation

Key Features

- Alarm on small traces of artificial gamma radiation
- Ideal for detection of shielded sources
- Weighs approx. 3 kg only
- One hand operation

The RadEye™ NBR is a combination of the Thermo Scientific RadEye SX multi-purpose meter and the FHZ 674 NBR detector. Even in case of large variations of the natural background during the search, very small contributions of artificial gamma radiation can be detected by a NBR detector (Natural Background Rejection). Especially for shielded or remote gamma sources, the RadEye NBR system will generate unambiguous audible and visual alarm indication within seconds, even if the incremental dose rate is just in the order of 0,01 $\mu\text{Sv/h}$ or less.

Compared to the well-known system FHT 40 NBR, battery operation time has been increased by 5 times, weight has been reduced by 1 kg and, as an additional

feature, the possible presence of artificial radiation is indicated on a 0 to 200 %-scaled bar graph (100 % = NBR alarm set point). This feature is extremely helpful during any active search mission. Furthermore, following multiple user suggestions, the audible indication for positive detection of artificial radiation is now well distinguished from the typically much more frequent gross gamma alarms that are caused by changing background conditions. Unlike the FHT 40 NBR, where the dose rate range is extended up to 1 Sv/h (FH 40 G-10 as control unit), the RadEye NBR dose rate range is limited to 100 $\mu\text{Sv/h}$. For higher dose rates, the use of an additional gamma survey meter (e.g. the RadEye G-10) is recommended.

The RadEye NBR system # 4250751 consists of RadEye and FHZ 674 NBR

RadEye SX Specifications

Order number	# 4250693
Measured quantities (with FHZ 674 NBR)	Count rate (cps, cpm), dose rate (Sv/h, rem/h), NBR
Probe cables	RG 58, max. 1.5 m (59") – MHV connector.
High voltage range	300 V...1400 V with output impedance 2 MΩ, typically 600 V for FHZ 674 NBR
Probe library	16 different detectors with corresponding high voltage, calibration factor, dead time correction, overload threshold, detector area and timeout for detector failure.
Alarm threshold	Two alarm thresholds for count rate, dose and dose rate each, NBR
Audible alarm intensity	80 dB at a distance of 30 cm (11.8").
Working temperature	-20 °C ... + 50 °C (-4 °F ... 122 °F).
Scaler/Timer	Preset count, preset time.
EMC	Disturbance emission: EN 61000-6-3, Immunity: EN 61000-6-2.
Size	110 mm x 67 mm x 62 mm (4.3" x 2.6" x 2.4"), with rubber protection, without cable.
Weight	Around 160 g (5.6 oz) including 2 ea. AAA cells and protection sleeve.
Internal memory	The last 1600 measured values are saved and can be read out via PC program. Max and mean value of count rate and dose rate. The time interval is factory preset to 120 s by default. As well scaler measurements and momentaneous readings can be stored manually. Logbook with 250 entries for changes of configuration, occurring alarms and errors.
Battery life time	Typically 150 h with FHZ 674 NBR.

For detailed information about the Radeye SX and the connectivity options of further probes please ask for a separate data sheet.

FHZ 674 NBR Specifications

Order number	# 4250750
Detection Sensitivity	approx. 4000 cps per μSv/h at 662 keV, highly sensitive from 15 keV (front), respectively 30 keV (side)
Energy response (H*(10))	Exceeds IEC 62533* requirements (+/- 30 % for Am-241, Cs-137, Co-60).
Dose rate range (Cs-137)	0.01 μSv/h to 100 μSv/h
Weight	2800 g excluding shoulder strap (200 g) and RadEye SX (160 g)
Dimensions	308 mm x 230 mm x 110 mm

*IEC 62533 Highly sensitive hand-held instruments for photon detection of radioactive material.

Recommended alternative test adapters for HV-fine adjustment and test indication of artificial (= non-background) gamma alarms.

Exempt check source Cs-137	3.7 kBq (0.1 μCi), sealed in a 1" resin chip	# SM149479010
Lutetium Test Adapter 50 g Lu ₂ O ₃	approx. 50 Bq/g Lu-176, 62 mm dia. chip (aluminium housing)	# 4254948
Lutetium Test Adapter 36 g Lu ₂ O ₃	approx. 50 Bq/g Lu-176; for use with Radeye PRD as well	# 425067071



NBR = Natural Background Rejection

The NBR measurement method has been developed by Thermo Fisher Scientific, for extremely fast discrimination between natural and artificial gamma radiation. More than 2,000 devices, based on this technology, are in use worldwide.

© 2012 Thermo Fisher Scientific Inc. All rights reserved. Windows is a registered trademark of Microsoft Corporation in United States and other countries. All other trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Results may vary under different operating conditions. Thermo Fisher Scientific makes no warranties, expressed or implied, in this product summary. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representatives for details. 120104_DB_RadEyeNBR-e-V1.0.

Europe, Africa, Middle East & Countries Not Listed

Frauenauracher Strasse 96 +49 (0) 9131 998-226
 D 91056 Erlangen, Germany +49 (0) 9131 998-172 fax
 customerservice.eid.erlangen@thermofisher.com

China

7th Floor, Tower West, Yonghe Plaza +86 10 8419 3588
 No. 28 Andingem E. Street, Beijing, 100007 China +86 10 8419 3581 fax
 info.eid.china@thermofisher.com

Singapore

11 Biopolis Way, Helios, Units #12-07/08 +65 6478 9728
 Singapore 138667 +65 6478 9505 fax
 info.eid.singapore@thermofisher.com

United Kingdom

Bath Road, Beenham, +44 (0) 118 971 5042
 Reading RG7 5PR United Kingdom +44 (0) 118 971 2835 fax
 customerservice.eid.beenham@thermofisher.com

USA, Canada, Mexico, Central & South America

27 Forge Parkway +1 (508) 553 1700
 Franklin, MA 02038 USA +1 (800) 274 4212 US toll-free
 info.eid@thermofisher.com +1 (508) 520 2815 fax

India

Plot No. C -327, T.T.C. Industrial Area, Pawne +91-22-41578800
 Navi Mumbai 400 705, India +91-22-41578801 fax
 info.eid.india@thermofisher.com

www.thermoscientific.com/rmp